



Protective Surface Treatment and Hardener for Concrete and Masonry

RECOMMENDATION

AQUABAN 500 is recommended for use in combination with **AQUABAN 400** where excessive chemical exposure, concentrated deicing solutions, and heavy abrasive traffic are present.

SURFACE PREPARATION

Apply **AQUABAN 400** according to PennKote specifications and allow to dry.

APPLICATION

Apply one coat of **AQUABAN 500** with brush, roller or spray at the uniform rate of 400 sq.ft. per gallon.

DRYING TIME

Active when dry to touch.

CONTAINERS

One gallon, five gallon and 45 gallon drums.

AVAILABILITY

Manufactured in Canada. Also available from selected distributors throughout Canada and the United States. Contact PennKote for your nearest source of supply.

PROPERTIES

AQUABAN 500 is a water soluble inorganic polymer based on sodium fluoro silicate which interacts with **AQUABAN 400** to provide additional chemical resistance while hardening the surface.

WARRANTY

PennKote Ltd. warrants its products against manufacturing and material defects. PennKote will, for a period of two years from the date of application, supply replacement material for product proven to be defective. This warranty is in lieu of any and all other warranties expressed or implied. Pennkote Ltd. and any Distributor or Retailer of this product accept no liability for incidental or consequential damage due to defective material or improper installation. The user shall determine the suitability of this product for intended use.