



Impregnating Waterproof Treatment for Wood

DESCRIPTION

AQUABAN 700 is a clear, penetrating solution specifically designed to provide a water repellent finish for wood. In addition to its waterproofing qualities, AQUABAN 700 will renew the original look of old, weathered wood as well as enhance and prolong the beauty of new wood. AQUABAN 700 is virtually unaffected by airborne industrial pollutants, ozone, or ultra- violet light.

SURFACE PREPARATION

Remove all loose material, dust, dirt and grease. Surface must be completely dry.

APPLICATION

Product is ready to use from the container. Apply with brush or airless spray at the uniform rate of 100 - 200 sq.ft. per gallon, depending on the porosity of the substrate. AQUABAN 700 is quickly absorbed into the surface and the water repellent effect will extend well below the surface of the substrate.

DRYING TIME

Active when dry to touch.

CONTAINERS

One gallon, five gallon and 45 gallon drums.

AVAILABILITY

Manufactured in Canada. Also available from selected distributors throughout Canada and the United States. Contact PennKote for your nearest source of supply.

PROPERTIES

AQUABAN 700 is a complex aluminum stearate solution. The product renders a surface water repellent but does not seal it completely so that, although the permeability of the substrate is slightly lowered, a treated surface will still allow the passage of air and water vapour. Long term weathering tests followed by water absorption tests reveal that AQUABAN **700** retains 97% of its original water repellent qualities after 5 years.

CAUTION

Product is flammable and should not be used near open flame or sparks. Wear protective goggles and gloves when applying. Keep container tightly sealed. Store in cool environment.

WARRANTY

PennKote Ltd. warrants its products against manufacturing and material defects. PennKote will, for a period of two years from the date of application, supply replacement material for product proven to be defective. This warranty is in lieu of any and all other warranties expressed or implied. Pennkote Ltd. and any Distributor or Retailer of this product accept no liability for incidental or consequential damage due to defective material or improper installation. The user shall determine the suitability of this product for intended use.

Phone:905.683.6447