

TECHNICAL DATA SHEET

PENNMARINE

1

DESCRIPTION

PENNMARINE is high solids water based synthetic rubber compound based on acrylic elastomeric.

PENNMARINE has been specially designed for deck surfaces, super structures etc., of boats, yachts, cruisers, commercial vessels etc. It is supplied as a single component thixotropic soft paste which is easily applied by brush or spray to form upon drying, hard wearing, water tight, non-slip and durable surface. This flexible coating will effectively bond to and protect wood, polyester. canvas. metal, bitumen and other common materials from water, salt, ozone and rapid temperature changes.

APPLICATION DATA

Prepare surface by removing all loose material, dust, dirt and grease. All surfaces must be dry. On metal, apply one coat of **PENNPRIMER** metal. Wooden decks, polyester and previously painted surfaces, apply one coat of **PENNSEALER** after sanding. Dirty and contaminated surfaces must be cleaned with diluted muriatic acid, detergent and water. On "Vertical surfaces", apply at least one coat uniformly by brush or spray at the maximum rate of 2 sq.m/litre (100 sq.ft/gallon).On horizontal surfaces, apply two coats. Gaps and joints: Use **PENNFLEX** reinforcing fabric.

Cleaning brushes and tools: Immediately after use, wash with water, or with varsol or xylene when dry and hard.

For more information on application and properties of this material contact the manufacturer.

This waterbased material is non-flammable and does not contain volatile or harmful vapours. It is safe to use in enclosed areas. **Protect from Freezing. Keep out of the reach of children.**

<u>WARRANTY</u>

PennKote Ltd. warrants its products against manufacturing and material defects. PennKote will, for a period of two years from the date of application, supply replacement material for product proven to be defective. This warranty is in lieu of any and all other warranties expressed or implied. Pennkote Ltd. and any Distributor or Retailer of this product accept no liability for incidental or consequential damage due to defective material or improper installation. The user shall determine the suitability of this product for intended use.

26/04/2007